4"

201M

**White Text,
5/8" Ht., Raised**
Text Requirements per ADA:
*Text raised from sign surface,
min. 1/32".
Separated 3/8" min from
Braille.*

**Braille, Grade 2, Domed,
Material to Match Adjacent
Panel**
*Braille Requirements per
ADA:*
*Located directly below
associated text.*

2"

Min.
3/8"

Min.
3/8"

0   0.25   0.5   1
INCHES

9" to center
of sign

201M

4'-6" Typ.
If not feasible, refer to notes about current OSA codes.

Typical sign location
Not to scale

SIGN SPECIFICATIONS
Sign Material and Colors:
Acrylic, 1/8" th. Matches Standard Black, matte surface.
Text: White. Raised.

Fonts:
Arial regular

NOTES:
1. CSU Facilities Management Environmental Graphic Designer to provide EPS files for fabrication.
2. Contractor to provide shop drawings of all signs for review and approval by CSU Facilities Management Environmental Graphic Designer prior to fabrication and installation.
3. Braille graphics are for illustrative purposes only. Actual Braille to be composed by signage fabricator. All Braille text should be verified before fabrication.
4. Signage material, colors, and fonts may match existing or proposed interior signage system as long as these are in accordance with current OSA Adopted Codes and Standards for Accessible Design per the Americans with Disabilities Act (ADA). However, all symbols and wordings must follow this standard.
5. Any deviations from these standards must be in accordance with the current OSA Adopted Codes and Standards for Accessible Design per the ADA.
6. Signs shall be located to meet current OSA Adopted Codes and Standards for Accessible Design per the ADA.
7. Installation varies per building and wall finish. Some walls will require fasteners instead of adhesive. Any fastener should not impede sign content. Paint fastener to match sign background.

CSU Interior Signage Standards:
www.fm.colostate.edu/constr_standards